

**THE TOUGHEST
PERFORMER**
«FOR YOUR FIELD»

WT 90



4 CYLINDER TURBO
CHARGED ENGINE

12F+12R SYNCHROMESH
TRANSMISSION

HEAVY LIFT
CAPACITY

POWER
STEERING

HEAVY DUTY
2WD/4WD



**COST
EFFICIENT**
MECHANICAL TRACTORS

MADE OF
**REAL
STEEL**

STRATEGIC
COLLABORATION
WITH
YANMAR



WT 90

FEATURES	Sonalika WT 90 (4WD)
ENGINE	
Engine Type	ITL Engine (4105FLT)
HP Category	90
No. of Cylinders	4
Aspiration	Turbo charged with intercooler
Cubic Capacity (cc)	4087
Rated RPM	2200
Air cleaner	Dry Type
Cold Start	Standard
Max Torque (nm) (+/- 5%)	339 @1300
Exhaust	Underhood Downdraft Silencer Underhood Upward
TRANSMISSION	
Drive	4WD
Clutch	Double Clutch
Gearbox	12F+12R
Transmission	Synchronmesh
SPEED (FORWARD)	
Maximum Speed (Km/Hr)	34.87
Minimum Speed (Km/Hr)	1.62
BRAKES	
Brakes	Oil Immersed Brakes
Type of actuation	Mechanical
Parking Brake	Independent Type

FEATURES	Sonalika WT 90 (4WD)
DIFFERENTIAL LOCK	
Differential lock	Mechanical, Foot Operated
PTO	
PTO (RPM)	540/540E (Standard) 540/1000 (Optional)
PTO (Actuation)	Mechanical
STEERING	
Steering	Power
ELECTRICAL	
Battery	12V 110 AH
Alternator	12V, 36Amps
Seven pin trailer socket	Standard
HYDRAULICS	
3 point linkage	CAT-II
Stay Bars	Adjustable
Hydraulic Lifting Capacity (Kg)	2500 (3000 Optional)
Auxiliary Hydraulic circuit	2DA/2SA
Lift Rods	Standard
SAFETY SWITCH	
Clutch Safety Switch	Standard
PTO Safety Switch	Standard
Neutral Safety Switch	Standard
CAPACITY (LTRS)(+/-5%)	
Fuel tank (Ltr)	75
TURNING RADIUS	
Without Brakes (m)	LHS-6.13, RHS-6.18
TYRE	
Front	12.4*24
Rear	18.4*30
DIMENSION & WEIGHT(+/-5%)	
Weight(kg)	3565
Wheel Base (mm)	2340
Total Length (mm)	4037-4390
Total Width (mm)	2400
Height (mm) up to ROPS	2803 (ROPS)
Min. Ground Clearance (mm)	398
Front Track (mm)	1670
Rear Track (mm)	1508



FEATURES	Sonalika WT 90 (4WD)
OTHERS	
Fuel Indicator gauge	Standard
Front Tow Hook	Standard, inbuilt in front weight
Front & Rear Weights with Std. Ballast	Optional Front Weights: Option 1 : 72 + 6*31 Kg Option 2 : 72 + 8*31 Kg Option 3 : 72 + 10*31 Kg Optional Rear Weights: Option 1 : 1*34 On Each Wheel Option 2 : 2*34 On Each Wheel
Trailer Hitch	Swinging Drawbar
ROPS	Standard
HVAC Cabin	Optional

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP



SONALIKA FAMAG S.P.A

Address: Industrial Area, N7, Sidi Bel Abbès, Algeria, Phone: +213(0)48 70 35 03

URL: <https://sonalika-famag.com>