



**THE TOUGHEST
PERFORMER**
« FOR YOUR FIELD »

**DI-75
RX 2WD**



HIGH TORQUE
ENGINE

8F+2R
TRANSMISSION®

HEAVY LIFT
CAPACITY

POWER
STEERING

HEAVY DUTY
2WD/4WD



**COST
EFFICIENT**

MECHANICAL TRACTORS

MADE OF

**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH**

YANMAR

**THE TOUGHEST
PERFORMER
« FOR YOUR FIELD »**

**DI-75
RX 2WD**

| FEATURES | Sonalika DI-75 RX 2WD |
|------------------------|--------------------------|
| ENGINE | |
| Engine Type | ITL Engine (4100 FLT) |
| HP Category | 75 |
| No. of Cylinders | 4 |
| Aspiration | Turbo Charged |
| Cubic Capacity (cc) | 3707 |
| Rated RPM (+/-25mm) | 2200 |
| Air Cleaner | Dry Type |
| Cold Start | Standard |
| Max Torque (Nm) | 278 1200±100 |
| Exhaust | Updraft (Elliptical) |
| TRANSMISSION | |
| Drive | 4WD |
| Clutch | Dual, Dry Friction Plate |
| Gearbox | 8F+2R |
| Front Axle | 4WD |
| Transmission | Constant Mesh |
| SPEED (FORWARD) | |
| Maximum Speed (Km/Hr) | 34.46 |
| Minimum Speed (Km/Hr) | 1.95 |

| FEATURES | Sonalika DI-75 RX 2WD |
|--------------------------------------|-----------------------|
| BRAKES | |
| Brakes | Oil Immersed Brake |
| Type of Actuation | Mechanical |
| Parking Brake | Independent Type |
| DIFFERENTIAL LOCK | |
| Differential Lock | Standard |
| PTO | |
| PTO (RPM) | 540@1680ERPM |
| STEERING | |
| Steering | Power |
| ELECTRICAL | |
| Battery | 12V 110AH |
| Alternator | 12V, 36 AMP |
| Seven Pin Trailer Socket | Standard |
| HYDRAULICS | |
| 3 Point Linkage | CAT-II |
| Stay Bars | Swinging Drawbar |
| Hydraulic Lifting Capacity (Kg) | 2000 |
| Auxiliary Hydraulic Circuit | 1SA/1DA |
| Lift rods | Standard |
| SAFETY SWITCH | |
| Neutral Safety Switch | Standard |
| CAPACITY (LTRS)(+/-5%) | |
| Fuel tank (Ltr.) | 62 |
| TYRE | |
| Front | 12.2*24 |
| Rear | 16.9*30 |
| DIMENSION & WEIGHT(+/-5%) | |
| Weight (Kg) | 2630 |
| Wheel Base (mm) | 2130 |
| Total Length (mm) | 3740-4090 |

SONALIKA FAMAG



| FEATURES | Sonalika DI-75 RX 2WD |
|--|--|
| Total Width (mm) | 1910-2250 |
| Height (mm) Up to ROPS | 2760 (ROPS) |
| Min Ground Clearance (mm) | 334 |
| Front Track (mm) | 1380 |
| Rear Track (mm) | 1510 |
| OTHERS | |
| Fuel Indicator Gauge | Standard |
| Front Toe Hook | Standard, Inbuilt in Front Weight |
| Front & Rear Weights With Std. Ballast | Front-72 Kg Base Wt+6x31, Rear-1x34 on Each Wheel |
| Trailer Hitch | Swinging Drawbar |

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP



SONALIKA FAMAG S.P.A

Address: Industrial Area, N7, Sidi Bel Abbès, Algeria, Phone: +213(0)48 70 35 03

URL: <https://sonalika-famag.com>