

**HEAVY DUTY
TRACTOR RANGE**
«FOR YOUR FIELD»

**N75
4WD**

ORCHARD/VINEYARD
FARMING SPECIALIST

HIGH TORQUE
ENGINE

HEAVY LIFT
CAPACITY

CARRARO
DRIVE LINE

HVAC/HEATER
CABIN (OPTIONAL)








**COST
EFFICIENT**
MECHANICAL TRACTORS










MADE OF
**REAL
STEEL**

**STRATEGIC
COLLABORATION
WITH
YANMAR**

HEAVY DUTY TRACTOR RANGE FOR YOUR FIELD



N75
4WD

| FEATURES | Sonalika N 75 |
|--|---|
| ENGINE  | |
| Engine Type | 4 Cylinder Turbocharged Engine |
| HP Category | 75 |
| No. of Cylinders | 4 |
| Aspiration | Turbocharged |
| Cubic Capacity (cc) | 3707 |
| Rated RPM | 2000 / 2200 |
| Air Cleaner | Dry Air Cleaner with Clogging Sensor |
| Cold Start | Standard |
| Max Torque (Nm) | 278 @ 1200±100 |
| Exhaust | Underhood Downdraft Towards the Floor |
| TRANSMISSION  | |
| Clutch | Double Clutch |
| Gearbox | 12F+12R |
| Front Axle | 4WD |
| Transmission | Synchromesh Shuttle Transmission with Creeper |
| SPEED (FORWARD)  | |
| Maximum Speed (Km/Hr) | 31.10@2000 erpm |
| Minimum Speed (Km/Hr) | 0.5@2000 erpm |
| BRAKES  | |
| Brakes | Oil Immersed Brake |
| Type of Actuation | Mechanical |
| Parking Brake | Independent Type |
| DIFFERENTIAL LOCK  | |
| Differential Lock | Yes, Foot Operated |

| FEATURES | Sonalika N 75 |
|--|-----------------|
| PTO  | |
| PTO (RPM) | 540/540E |
| PTO (Actuation) | Mechanical |
| STEERING  | |
| Steering | Power |
| ELECTRICAL  | |
| Battery | 12V, 85Ah |
| Alternator | 12V, 85Amp |
| Seven Pin Trailer Socket | Standard |
| HYDRAULICS  | |
| 3 Point Linkage | CAT-II |
| Stay Bars | Standard |
| Hydraulic Lifting Capacity (Kg) | 2500 |
| Auxiliary Hydraulic Circuit | 2SA/2DA |
| SAFETY SWITCH  | |
| Clutch Safety Switch | Standard |
| PTO Safety Switch | Standard |
| Neutral Safety Switch | Standard |
| CAPACITY (LTRS)(+/-5%)  | |
| Fuel Tank (Lit.) | 73 |
| TURNING RADIUS  | |
| Without Brakes (m) | 4.7 (w/O brake) |
| TYRE  | |
| Front | 8-18 |
| Rear | 14.9-24 |
| DIMENSION (+/-5%) (4WD/2WD)  | |
| Weight (Kg) | 2710 |
| Overall Length (mm) | 4020-4245 |
| Overall Width (mm) | 1475-1606 |
| Overall Height (mm) | 2612 (ROPS) |
| Wheel Base (mm) | 2217 |
| Min. Ground Clearance (mm) | 253 |
| Front Wheel Track Agri (mm) | 1150-1286 |
| Rear Wheel Track Agri (mm) | 1082-1213 |

SONALIKA FAMAG



| FEATURES | Sonalika 75 N |
|--|--|
| OTHERS  | |
| Fuel Indicator Gauge | Standard |
| Front Tow Hook | Standard, Inbuilt in Front Weight |
| Front & Rear Weights with Std. Ballast | Front-72 kg + 6x31 kg Front Removal Weight. / Rear 1*30 kg at Each Wheel |
| Trailer Hitch | Swinging Drawbar |
| ROPS | Standard |
| OPTIONAL FEATURES  | |
| Tyres | 4WD 2WD |
| Cabin | HVAC |
| Front Mudguard | Standard |

*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE, Please correlate with latest updates, accessories shown may not be part of standard product.

DEALER STAMP

SONALIKA FAMAG S.P.A

Address: Industrial Area, N7, Sidi Bel Abbès, Algeria, Phone: +213(0)48 70 35 03

URL: <https://sonalika-famag.com>